

Technical Data Sheet

universal

GYPSUM BINDER (SZERELŐGIPSZ) for quick-set binding

Ready-mixed, fast setting binding plaster for interior use for professional and do-it-yourself alike.

Where to use	<p>Excellent for installation and fastening works in various areas for building and other construction projects:</p> <ul style="list-style-type: none"> - for affixing electric fittings, cables, sleeve pipes, distribution boxes and casings - for the installation of other fittings, pipes and similar fixtures - for repairs before painting, for filling holes, cracks, grouts, and other openings and fissures of the like - for fast installation of bolts, nails, drill holes, dowels and other similar fixtures - also suitable for repairing and fastening around the household 																		
Application	<p>Slowly pour the universal plaster into a bucket of clean water. After a few minutes of slackening mix the material with a low speed electric mixer to obtain a homogenous, lump-free, thick and pulpy mix. Do not add any foreign material. The mixed universal plaster should be used within approximately 8-10 minutes, before it starts to set. Do not use the material if it has already hardened! After use your tools should be rinsed with plenty of water. Not recommended for use in temperatures below +5°C.</p>																		
Substrate requirement	<p>The surface must be solid, clean and dry. Remove all loose and disintegrating particles, dust and contamination from the surface. Before applying another coat, and before painting or wallpapering the material must be completely dried out and hardened. After hardening, protect the surface from moisture and water in general, so as to preserve its strength. Not suitable for substrates in industrial areas subject to damp and moisture. If uncertain or if in doubt about the application and use, consult the manufacturer or the distributor.</p>																		
Technical data	<table border="0"> <tr> <td>Compressive strength:</td> <td>≥ 5 N / mm²</td> </tr> <tr> <td>Bending strength:</td> <td>≥ 3 N / mm²</td> </tr> <tr> <td>Water requirement:</td> <td>one part water for two parts universal plaster</td> </tr> <tr> <td>Pot life:</td> <td>approx. 8-10 minutes</td> </tr> <tr> <td>Spreading rate as per standard:</td> <td>approx. 1.000 l/t</td> </tr> <tr> <td>Resistance to fire:</td> <td>A1, non-combustible</td> </tr> <tr> <td>MSZ EN:</td> <td>13279</td> </tr> <tr> <td>Declaration of performance number:</td> <td>109511</td> </tr> <tr> <td>Tariff heading:</td> <td>32149000</td> </tr> </table>	Compressive strength:	≥ 5 N / mm ²	Bending strength:	≥ 3 N / mm ²	Water requirement:	one part water for two parts universal plaster	Pot life:	approx. 8-10 minutes	Spreading rate as per standard:	approx. 1.000 l/t	Resistance to fire:	A1, non-combustible	MSZ EN:	13279	Declaration of performance number:	109511	Tariff heading:	32149000
Compressive strength:	≥ 5 N / mm ²																		
Bending strength:	≥ 3 N / mm ²																		
Water requirement:	one part water for two parts universal plaster																		
Pot life:	approx. 8-10 minutes																		
Spreading rate as per standard:	approx. 1.000 l/t																		
Resistance to fire:	A1, non-combustible																		
MSZ EN:	13279																		
Declaration of performance number:	109511																		
Tariff heading:	32149000																		
Packaging	<p>Available in 20 kg paper bags, 54 bags/pallet, in heat-shrink wrapping in 5 kg plastic bags, 192 bags/pallet, in heat-shrink wrapping</p>																		
Storage	<p>In a covered place, in dry conditions, for approximately 12 months from the date of manufacture, in unopened bags</p>																		
Manufacturer Distributor	<p>Casea GmbH., Germany Széria-Trans Kereskedelmi és Szolgáltató Kft. H-1116 Budapest, Adony u. 7, Phone: +36-1-466-7758 H-5300 Karcag, Tilalmasi út 1, Phone: +36-59-311-333</p>																		

This data sheet was prepared to the best of our understanding. The data contained therein reflect our latest technical knowledge and observations. However, we shall not be held liable for the statutory provision of contents. Users shall honour any patent rights, and shall comply with the applicable laws and regulations at their own responsibility.